

deflexx plus

deflexx plus is a UV- stabilised high performance-adhesive tape for durable bonding of overlappings, joints and penetrations of sarking-, casing- and reconstruction-membranes. In&Out

Product guarantee: 10 years

Recommended system product: doitBau **devaioo, devekk, devapp**

Technical Facts as specified by DIN 4102-8

Carrier material	UV- stabilized spezial foil
Carrier color	Black
Adhesive	Acrylic dispersion (solvent free)
Adhesion intercarrier	Polyester armoring
Thickness	0,29 mm
Adherency	14 N/ 1 cm DIN EN 1938 (1996)
Temperature	-50 / +100 °C
UV-persistence	12 months (solar radiation Central Europe)
Aging resistance	Very good
Moisture resistance	Very good (rain proof)
Softening agent resistant	Very good

Get-up

Length of roll	25 m
Width of roll	60 mm
m ² / roll	1,5 m ²
kg / roll	approx. 0,45 kg
Reference number	600104

Guarantee

doitBau grants 10 years on all characteristics which are warranted in the manual. However, this guarantee is excluded,

- in case of a processing or usage which deviates from what is stated in the manual.
- in case of abnormal chemical and/or mechanical influences on the product.
- in case of multilayered lengths, if the lengths haven't got sufficient inner cohesiveness (insufficient load carrying capacity by separation of layers).
- for sauna and swimming pool construction.

Prior to using the product tackifying tests have to be conducted on site in any case. It is possible that this manual is inoperative due to recent changes in knowledge and development. The most valid manual can be found at www.doitBau.com