

detopp

detopp is an easy to lay ridge- and arris-roll for durable ventilation of the roof covering.
Recommended system product: doitBau **deflexx Plus**

Technical Facts as stated by DIN EN 13859-1

Material	PP/Alu-compound
Width of the visible pleated aluminium band	60 mm in a strength of 150my, approx. 5 mm creased at the ends as edge and corrosion protection
Aluminum pleating	approx. 30%
Butyl adhesive overall width	25 mm incl. protruding plastic liner
Center piece fabric	approx. 120 g/m ² (UV- stabilised with woven dashed line)
Ventilation shaft	approx. 190 m ² /m
Air permeability	equates DIN 4108 part 3
UV- stability	direct (indirect) irradiation for more than 2 (8) years
Temperature range	+5°C to +95°C
Color (border area)	brick-red / borwn / anthracite

Get-up

Length of roll	5 m
Width of roll	320 mm
m ² / roll	1,6 m ²
kg / roll	approx. 1,00 kg
Reference number	600210

Guarantee

doitBau grants 5 years on all characteristics which are warranted in the manual. However, this guarantee is excluded,

- in case of a processing or usage which deviates from what is stated in the manual.
- in case of abnormal chemical and/or mechanical influences on the product.
- in case of multilayered lengths, if the lengths haven't got sufficient inner cohesiveness (insufficient load carrying capacity by separation of layers).
- for sauna and swimming pool construction.

Prior to using the product tackifying tests have to be conducted on site in any case. It is possible that this manual is inoperative due to recent changes in knowledge and development. The most valid manual can be found at www.doitBau.com