

devaioo plus

devaioo can be used as multi-function length for between- and over- rafter insulation, roof restoration and as open diffusion vapor compensation length for interior- and exterior construction. With a two sided Butyl adhesive tape.

Product guarantee: 5 years

Recommended system product: doitBau **deflexx plus, defixx, detakk, deflexx, deplann, sealing mass DK**

Technical Facts as stated by DIN EN 13859-1

Product structure	3 – layers
Material adhesive tape (both sided)	Butyl
Material	Polypropylene
Color	black
Mass per unit area	190 g/m ²
Effective thickness	0,52 mm
Tensile strength	338 N/5cm (longitudinal)/ 237 N/5cm (transverse)
Ultimate elongation	56% (longitudinal)/ 65% (transverse)
Nail pull-out-strength	300 N (longitudinal)/ 280 N (transverse)
Sd-value	> 2,00 m
Resistance to water passageway	W 1 (2,00m head of water)
Fire behavior	E
Operation temperature	-40 / +90 °C
Outdoor weathering	3 months

Get-up

Length of roll	50 m
Width of roll	1,50 m
m ² / roll	75 m ²
kg / roll	approx. 13,0 kg
Reference number	600205

Guarantee

doitBau grants 10 years on all characteristics which are warranted in the manual. However, this guarantee is excluded,

- in case of a processing or usage which deviates from what is stated in the manual.
- in case of abnormal chemical and/or mechanical influences on the product.
- in case of multilayered lengths, if the lengths haven't got sufficient inner cohesiveness (insufficient load carrying capacity by separation of layers).
- for sauna and swimming pool construction.

Prior to using the product tackifying tests have to be conducted on site in any case. It is possible that this manual is inoperative due to recent changes in knowledge and development. The most valid manual can be found at www.doitBau.com