

defixx

defixx is a carrier free high performance-adhesive for pre-assembly and fixation of vapor control layers. The elastic special armoring stabilizes the adhesive film as well as developing extreme adherency on all common surfaces.

Recommended system product: doitBau **devapp, devaiioo, devekk**

Technical Facts as specified by DIN 4102-8

Adhesive Carrier material	Acrylate dispersion (solvent-free)
Adhesion intercarrier	Polyester armoring
Cover material	silicone paper
Thickness	0,20 mm
Adherency	14 N/ 1 cm DIN EN 1939
Shearing resistance dynamic	25 N / cm ²
Temperature	-40 °C / +120 °C
aging resistance	Very good
Plasticizer resistance	Very good
adhesive qualities	aggressive adhesion

Get-up

Length of roll	50 m
Width of roll	20 mm
m ² / roll	1,0 m ²
kg / roll	approx. 0,4 kg
Reference number	600105

Guarantee

doitBau grants 5 years on all characteristics which are warranted in the manual. However, this guarantee is excluded,

- in case of a processing or usage which deviates from what is stated in the manual.
- in case of abnormal chemical and/or mechanical influences on the product.
- in case of multilayered lengths, if the lengths haven't got sufficient inner cohesiveness (insufficient load carrying capacity by separation of layers).
- for sauna and swimming pool construction.

Prior to using the product tackifying tests have to be conducted on site in any case. It is possible that this manual is inoperative due to recent changes in knowledge and development. The most valid manual can be found at www.doitBau.com