

deflexx 60

deflexx 60 is a very elastic high performance - foil adhesive tape for durable bonding of connection and penetration with vapor control layers.

Product guarantee: 10 years

Recommended system product: doitBau **devapp, devaioo, deplann, Dichtmasse DK, detakk, defixx**

Technical Facts as stated by DIN 4102-8

Adhesive	Acrylate dispersion (solvent-free)
Adhesion carrier	LDPE- foil
Carrier color	Black
Adhesion intercarrier	Polyester armoring
Cover material	silicone paper brown
Thickness (without cover)	approx. 0,25 mm
Adherency	14 N/ 1 cm DIN EN 1939
Temperature	-40 / +100 °C
Aging resistance	Very good
Moisture resistance	good
Working temperature	> -10°C (Substrate has to be dry and ice free)

Get-up

Length of roll	25 m
Width of roll	60 mm
m ² / roll	1,5 m ²
kg / roll	approx. 0,75 kg
Reference number	600101

Guarantee

doitBau grants 10 years on all characteristics which are warranted in the manual. However, this guarantee is excluded,

- in case of a processing or usage which deviates from what is stated in the manual.
- in case of abnormal chemical and/or mechanical influences on the product.
- in case of multilayered lengths, if the lengths haven't got sufficient inner cohesiveness (insufficient load carrying capacity by separation of layers).
- for sauna and swimming pool construction.

Prior to using the product tackifying tests have to be conducted on site in any case. It is possible that this manual is inoperative due to recent changes in knowledge and development. The most valid manual can be found at www.doitBau.com