

## deplann 60

deplann 60 is a firm high performance - adhesive tape for durable, airtight bonding of vapor barriers for overlaps in interior applications. It is also possible to securely bond joint - connections of wood-based panels (e.g. OSB), as well as small holes and fissures.

Product guarantee: 10 years

Recommended system product: doitBau **devapp, devaioo, deplann, deflexx, Dichtmasse DK, detakk, defixx**

**Technical Facts** as stated by DIN 4102-8

Carrier material	coated specialty paper
Carrier color	White
Adhesive	Acrylate dispersion (solvent-free)
Thickness	0,28 mm
Adherence	14 N / 1 cm
Temperature	-40 / +100 °C
Aging resistance	Very good
Working temperature	> -10°C (Substrate has to be dry and ice free)

## Get-up

Length of roll	40 m
Width of roll	60 mm
m <sup>2</sup> / roll	2,4 m <sup>2</sup>
kg / roll	approx. 1,1 kg
Reference number	600100

## Guarantee

doitBau grants 10 years on all characteristics which are warranted in the manual. However, this guarantee is excluded,

- in case of a processing or usage which deviates from what is stated in the manual.
- in case of abnormal chemical and/or mechanical influences on the product.
- in case of multilayered lengths, if the lengths haven't got sufficient inner cohesiveness (insufficient load carrying capacity by separation of layers).
- for sauna and swimming pool construction.

Prior to using the product tackifying tests have to be conducted on site in any case. It is possible that this manual is inoperative due to recent changes in knowledge and development. The most valid manual can be found at [www.doitBau.com](http://www.doitBau.com)