

detakk

detakk elastic high performance-foam adhesive tape closes leakages which result from attaching roof control foils durable and airtight. It is also suitable for application in RLT-facilities as stated by VDI 6022. In&Out

Recommended system product: doitBau **devapp, devekk, devaioo**

Technical Facts as stated by DIN 4102-8

Carrier material	Modified Polyethylene-Foam
Carrier color	Black
Adhesive	Synthetic rubber
Covering material	firmly laminated silicone foil
Thickness	3 mm
Temperature	-30 / +80 °C
Condensation resistance	Very good
Unit Weight (ISO 845)	approx. 30 kg/m ³
Tensile strength (ISO 1926)	125 % (long)/ 115 % (width)
Elongation (ISO 1926)	98 kPa (ISO 844)
Compression hardness at 50% compression	98kPa (ISO 844)
Compression damage resistance (25% over 22h at 23°C)	20% (0,5h after relief) (ISO 1856-B) 12% (24h after relief)
Water absorption (7d)	<1 Vol.-%

Get-up

Length of roll	20 m
Width of roll	50 mm
m ² / roll	1,0 m ²
kg / roll	approx. 0,25 kg
Reference number	600106

Guarantee

doitBau grants 5 years on all characteristics which are warranted in the manual. However, this guarantee is excluded,

- in case of a processing or usage which deviates from what is stated in the manual.
- in case of abnormal chemical and/or mechanical influences on the product.
- in case of multilayered lengths, if the lengths haven't got sufficient inner cohesiveness (insufficient load carrying capacity by separation of layers).
- for sauna and swimming pool construction.

Prior to using the product tackifying tests have to be conducted on site in any case. It is possible that this manual is inoperative due to recent changes in knowledge and development. The most valid manual can be found at www.doitBau.com