

devapp 200

devapp 200 is an easy to lay high performance vapor control layer made of extremely tearproof polyethylene to create an airtight building shell. Also usable as screed foil.

Product guarantee: 10 years

Recommended system product: doitBau **deflexx, deplann, detakk, defixx, Dichtmasse DK**

Technical Facts as stated by DIN EN 13859-1

Product structure:	Multilayered special foil
Material:	modified polymere
Color:	Light blue
Heating value:	43 MJ/kg
Thickness:	0,170 mm
Sd-value:	> 100 m
Fire behavior:	E EN 13501-1
Temperature:	-30 / +70 °C

Get-up

Length of roll:	25 m
Width of roll:	4 m
m ² / roll:	100 m ²
kg/ roll:	approx. 14,85 kg
Reference number:	600200

Guarantee

doitBau grants 10 years on all characteristics which are warranted in the manual. However, this guarantee is excluded,

- in case of a processing or usage which deviates from what is stated in the manual.
- in case of abnormal chemical and/or mechanical influences on the product.
- in case of multilayered lengths, if the lengths haven't got sufficient inner cohesiveness (insufficient load carrying capacity by separation of layers).
- for sauna and swimming pool construction.

Prior to using the product tackifying tests have to be conducted on site in any case. It is possible that this manual is inoperative due to recent changes in knowledge and development. The most valid manual can be found at www.doitBau.com