

## devapp 250

devapp 200 easy to lay high performance vapor control layer made of extremely tearproof polyethylene to create an airtight building shell. Also usable as screed foil.

Product guarantee: 10 years

Recommended system product: doitBau **deflexx**, **deplann**, **detakk**, **defixx**, **demurr**

**Technical Facts** as stated by DIN EN 13859-1

Product structure	Multilayered special foil
Material	Modified polymere
Color	Light blue
Calorific value	58 MJ/kg
Thickness	0,210 mm
Sd-value	> 140 m
Fire behavior	E EN 13501-1
Temperature	-30 / +70 °C

### Get-up

Length of role	25 m
Width of roll	4 m
m <sup>2</sup> / roll	100 m <sup>2</sup>
kg / roll	approx. 19,9 kg
Reference number:	600201

### Guarantee

doitBau grants 10 years on all characteristics which are warranted in the manual. However, this guarantee is excluded,

- in case of a processing or usage which deviates from what is stated in the manual.
- in case of abnormal chemical and/or mechanical influences on the product.
- in case of multilayered lengths, if the lengths haven't got sufficient inner cohesiveness (insufficient load carrying capacity by separation of layers).
- for sauna and swimming pool construction.

Prior to using the product tackifying tests have to be conducted on site in any case. It is possible that this manual is inoperative due to recent changes in knowledge and development. The most valid manual can be found at [www.doitBau.com](http://www.doitBau.com)