

dewall 75

The one-sided adhesive tape from elastic high performance-foam. For a durable and airtight sealing of Walls. High sound insulation, extreme reserve capacity, long Life. B1 according to DIN 4102 for acoustic and thermal sealing of partition walls to Floor, wall and ceiling fittings, and metal parts to each other
Recommended system product: doitBau **devapp, devekk, devaioo**

Technical Facts as stated by DIN 4102-8

Carrier material	Modified Polyethylene-Foam
Carrier color	Black
Adhesive	Synthetic rubber
Covering material	firmly laminated silicone foil
Temperature	-30 / +80 °C
Unit Weight (ISO 845)	~ 30 kg/m ³
Water absorption (7d)	<1 Vol.-%
Thickness	3 mm

Get-up

Length of roll	30 m
Width of roll	75 mm
m ² / roll	2,25 m ²
kg / roll	0,6 kg
Reference number	600108

Guarantee

doitBau grants 2 years on all characteristics which are warranted in the manual. However, this guarantee is excluded,

- in case of a processing or usage which deviates from what is stated in the manual.
- in case of abnormal chemical and/or mechanical influences on the product.
- in case of multilayered lengths, if the lengths haven't got sufficient inner cohesiveness (insufficient load carrying capacity by separation of layers).
- for sauna and swimming pool construction.

Prior to using the product tackifying tests have to be conducted on site in any case. It is possible that this manual is inoperative due to recent changes in knowledge and development. The most valid manual can be found at www.doitBau.com